



# GARDEN 4T SAE 30

4 Stroke Engine Oil for Motorized Garden Tools

SAE 30

## TYPE OF USE

**Specially formulated for motorized garden tools and small farming equipment.**

**All Gasoline & Diesel 4 Stroke Engines.**

Lawn mowers, motor mowers, tillers, light tractors,...

Suitable for all type of fuels: leaded and unleaded gasoline, Diesel fuel, Ethanol, biofuels.

All types of 4 stroke engines with or without catalytic converter.

## PERFORMANCE

STANDARDS                      API SG / CD

Ensures the engine cleanliness.

Protection during wintering.

Dispersant and detergent properties.

Good cold starting, perfectly stable in hot engine.

Anti-wear, Anti-oxidation properties.

Anti-corrosion, Anti-foam properties.

## RECOMMENDATIONS

Oil change: According to manufacturers' requirements and tune to your own use.

MOTUL GARDEN 4T SAE 30 can be mixed with synthetic or mineral lubricants.

## PROPERTIES

Viscosity grade	SAE J300	<b>30</b>
Density at 20°C (68°F)	ASTM D1298	0.879
Viscosity at 40°C (104°F)	ASTM D445	89.1 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	10.7 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	101
Flash point	ASTM D92	240°C / 464°F
Pour point	ASTM D97	-29°C / -20°F
TBN	ASTM D2896	7.6 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.      Made in FRANCE.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - Web Site: [www.motul.com](http://www.motul.com)

03/16